



## SX 125 - TECHNICAL SPECIFICATIONS

<b>ENGINE</b>	Aprilia single-cylinder, 4 stroke.
<b>DISPLACEMENT</b>	124,8 cc
<b>MAXIMUM POWER</b>	11 kW
<b>MAXIMUM TORQUE</b>	22.2 Nm @ 8000 rmp
<b>COOLING</b>	Liquid cooling
<b>FRONT SUSPENSION</b>	Ø40 mm USD fork. Wheel travel: 260 mm.
<b>REAR SUSPENSION</b>	Steel swingarm. Hydraulic monoshock absorber. Wheel travel: 265 mm
<b>FRONT BRAKE</b>	Stainless steel disc (Ø 260 mm). Floating caliper. Metal braided brake line. ABS BOSCH 9.1 ML.
<b>REAR BRAKE</b>	Stainless steel disc (Ø 220 mm) with single piston caliper. Metal braided brake line.
<b>FRONT TYRE</b>	110/70 R 17
<b>REAR TYRE</b>	150/60 R 17
<b>SEAT HEIGHT C31</b>	870 mm
<b>FUEL TANK</b>	10 lt (3 lt reserve)
<b>EMISSIONS</b>	Euro 3 homologation
<b>ENGINE</b>	Aprilia single-cylinder, 4 stroke.
<b>DISPLACEMENT</b>	124,8 cc
<b>MAXIMUM POWER</b>	11 kW
<b>MAXIMUM TORQUE</b>	22.2 Nm @ 8000 rmp
<b>COOLING</b>	Liquid cooling
<b>FRONT SUSPENSION</b>	Ø40 mm USD fork. Wheel travel: 260 mm.
<b>REAR SUSPENSION</b>	Steel swingarm. Hydraulic monoshock absorber. Wheel travel: 265 mm
<b>FRONT BRAKE</b>	Stainless steel disc (Ø 260 mm). Floating caliper. Metal braided brake line. ABS BOSCH 9.1 ML.
<b>REAR BRAKE</b>	Stainless steel disc (Ø 220 mm) with single piston caliper. Metal braided brake line.
<b>FRONT TYRE</b>	110/70 R 17
<b>REAR TYRE</b>	150/60 R 17
<b>SEAT HEIGHT C31</b>	870 mm
<b>FUEL TANK</b>	10 lt (3 lt reserve)
<b>EMISSIONS</b>	Euro 4